

LiteBar



Raising the Bar

Reduce Labor & Increase Profit with Litebar,
Call us today at 701-509-6691

www.360SalesLLC.com



Raising the Bar

Manufactured with high quality glass fiber with polyester resin or optional vinyl ester resin. LiteBar is built to be stronger, lighter, and rust free! LiteBar is non-magnetic, making it electrically non-conductive as well as thermally non-conductive. Packaged in 50 piece bundles for easy shipping and handling.



RUST FREE

Does not corrode, extended structure life



LIGHTWEIGHT

Large labor & freight savings



NON-CONDUCTIVE

LiteBar is electrically non-conductive and thermally non-conductive



STRONGER THAN STEEL

LiteBar outperforms traditional black bar in all ASTM testing criteria



INSTALLS LIKE STEEL

Tie it off and chair it up just like steel!

	#4	#5
Nominal Diameter Area	7/16 in (.150in ²)	9/16 in (.240in ²)
Lengths	Up to 20 ft	Up to 20 ft
Weight	.128 lbs/ft	.19 lb/ft
Ultimate Tensile Strength ASTM 7205	126 ksi 869 MPa	110 ksi 764 MPa
Ultimate Tensile Load ASTM 7205	18,884 lbs 84.3 kN	26,302 117 kN
Tensile Modulus of Elasticity ASTM 7205	6,450 ksi 44.5 GPa	6,140 ksi 42.3 GPa
Guaranteed Transverse Shear Capacity ASTM 7617	21.1 ksi 145.5 MPa	21.1 ksi 145.5 MPa
Moisture Content ASTM D570	<.5%	<.5%
Fiber Content	>80% by wt.	>80% by wt.

**ICC-ES pending*